

**SPÉCIFICATIONS / SPECIFICATIONS****CM-308E****CM-303E**

<b>Moteur de l'arbre</b> Cutter head motor	<b>3 CV / 230 V / 60 C / 1 Ph ou</b> <b>3 CV / 600 V / 60 C / 3 Ph</b> 3 HP / 230 V / 60 Hz / 1 Ph or 3 HP / 600 V / 60 Hz / 3 Ph	<b>3 CV / 230 V / 60 C / 1 Ph ou</b> <b>4 CV / 600 V / 60 C / 3 Ph</b> 3 HP / 230 V / 60 Hz / 1 Ph or 4 HP / 600 V / 60 Hz / 3 Ph
<b>Largeur maximale de travail</b> Maximum working width	<b>203 mm</b> 8"	<b>305 mm</b> 12"
<b>Épaisseur maximale de coupe</b> Maximum cutting depth	<b>15 mm</b> 0,6"	<b>15 mm</b> 0,6"
<b>Vitesse de l'arbre de la tête de coupe</b> Saw arbor's speed	<b>5000 RPM</b>	<b>5000 RPM</b>
<b>Diamètre de la tête de coupe</b> Saw arbor diameter	<b>100 mm</b> 4"	<b>100 mm</b> 4"
<b>Dimensions des pastilles de la tête de coupe</b> Inserts' dimensions	<b>14 x 14 x 2 mm (x60)</b> 0,5" x 0,5" x 0,8" (x60)	<b>14 x 14 x 2 mm (x90)</b> 0,5" x 0,5" x 0,8" (x90)
<b>Dimensions de la table</b> Table's dimensions	<b>1810(L) x 203(P) mm</b> 71,25"(L) x 8"(W)	<b>2020(L) x 305(P) mm</b> 79,5"(L) x 12"(W)
<b>Hauteur de la table</b> Table's height	<b>800 mm</b> 31,5"	<b>800 mm</b> 31,5"
<b>Angle du guide</b> Guide angle	<b>90° ~ -45°</b>	<b>90° ~ -45°</b>
<b>Dimensions de la machine</b> Machine's dimensions	<b>1845(L) x 635(P) x 940(H) mm</b> 72,5"(L) x 25"(W) x 37"(H)	<b>2040(L) x 840(P) x 1000(H) mm</b> 80"(L) x 33"(W) x 39"(H)
<b>Dimensions de l'emballage</b> Packing's size	<b>1990(L) x 660(P) x 980(H) mm</b> 78,25"(L) x 26"(W) x 38,5"(H)	<b>2130(L) x 710(P) x 940(H) mm</b> 84"(L) x 28"(W) x 37"(H)
<b>Poids net</b> Net weight	<b>400 kg / 880 lb</b> 400 KGs / 880 lbs.	<b>440 kg / 968 lb</b> 440 KGs / 968 lbs.
<b>Poids brut</b> Gross weight	<b>455 kg / 1001 lb</b> 455 KGs / 1001 lbs.	<b>490 kg / 1078 lb</b> 490 KGs / 1078 lbs.